





420 diode LED light sheet  
(single cuttable)

## OVERVIEW

### FRONT VIEW



### ACCESSORIES



## SPECIFICATIONS

### PHYSICAL SPECIFICATIONS

<b>Part Number</b>	431100
<b>Model #</b>	LSM24-A
<b>Chip</b>	Legacy
<b>CRI</b>	85+
<b>LED / Sheet</b>	420 pieces
<b>Color Temperature</b>	4100 K • 5300 K • 6500 K
<b>Lumens</b>	1600 lm/sheet
<b>Operating Temperature</b>	-30 °C (-22 °F) ~ +50 °C (+122 °F)
<b>Environment</b>	Wet-rated - conforms to IP65 standard for the sheet. (To maintain wet rating, the provided silicone must be placed over all connection points, and also over any area that has been cut)
<b>Mounting</b>	3M adhesive backing
<b>Size of sheet</b>	500 mm x 250 mm
<b>Minimum Size</b>	Minimum cuttable size of 0.47" x 0.47"
<b>Maximum Size</b>	Class 2: Maximum tiling max 7 sheets based on 96W driver,
<b>Depth</b>	Bumper height - 8mm • Overall depth of the system (including bumper) - 8.75mm
<b>Weight</b>	0.3 lb/sheet
<b>Accessories</b>	Includes connection wires and hardwire cables with 2-pin connector male plug and a plug-in adapter cable with 2.1mm/5.5mm female barrel connector and silicone

### ELECTRICAL SPECIFICATIONS

<b>Input Voltage</b>	24V DC
<b>Power Consumption</b>	12 W/Sheet
<b>LED Forwarding Voltage</b>	18V DC
<b>LED Forwarding Current</b>	1.2 mA
<b>Wire Size</b>	20 AWG cable with 2 pin connectors and 2.1/5.5 mm DC barrel connector
<b>Wiring</b>	20 AWG cable with 2 pin connectors and 2.1/5.5 mm DC barrel connector
<b>Connector</b>	12 integrated 2-pin connector blocks
<b>Certification</b>	UL listed (E346146), CE, RoHS